

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx BVS 14.0075X issue No.:0 Certificate history: _____

Status: **Current**

Date of Issue: **2014-08-14** Page 1 of 5

Applicant: **Herforder Elektromotoren-Werke GmbH & Co. KG**
Goebenstraße 106
32051 Herford
Germany

Electrical Apparatus: **Flameproof electric motors type D*Ex*** ***/**** ****
Optional accessory:

Type of Protection: **Equipment protection by flameproof enclosures "d", Equipment dust ignition protection by enclosure "t", Equipment protection by increased safety "e"**

Marking: Ex d IIC T* Gb resp. Ex de IIC T* Gb or
Ex d IIB T* Gb resp. Ex de IIB T* Gb. or
Ex tb IIIC T* °C Db
*) See Parameters

Approved for issue on behalf of the IECEx
Certification Body:

Dr. F Eickhoff

Position:

Deputy Head of Certification Body

Signature:
(for printed version)

Date:


2014-08-14

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](http://www.iecex.com).

Certificate issued by:

DEKRA EXAM GmbH
Dinnendahlstrasse 9
44809 Bochum
Germany

 **DEKRA**
DEKRA EXAM GmbH



IECEX Certificate of Conformity

Certificate No.: IECEx BVS 14.0075X

Date of Issue: 2014-08-14

Issue No.: 0

Page 2 of 5

Manufacturer: **Herforder Elektromotoren-Werke GmbH & Co. KG**
Goebenstraße 106
32051 Herford
Germany

Additional Manufacturing location
(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Edition: 6.0	Explosive atmospheres - Part 0: General requirements
IEC 60079-1 : 2007-04 Edition: 6	Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
IEC 60079-31 : 2008 Edition: 1	Explosive atmospheres – Part 31: Equipment dust ignition protection by enclosure 't'
IEC 60079-7 : 2006-07 Edition: 4	Explosive atmospheres - Part 7: Equipment protection by increased safety "e"

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

[DE/BVS/ExTR14.0077/00](#)

Quality Assessment Report:

[DE/BVS/QAR14.0009/00](#)



IECEX Certificate of Conformity

Certificate No.: IECEX BVS 14.0075X

Date of Issue: 2014-08-14

Issue No.: 0

Page 3 of 5

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

General product information:

Flameproof electric motors type D*Ex*** ***/**** **

Type designation to D^{*1)}Ex^{*2)}*2)*2) *3)*3)*3)/*4)*4)*4) *5)*5)*5)

1): Explosion group

- B: Flameproof enclosure for group IIB
- C: Flameproof enclosure for group IIC
- D: Flameproof enclosure for group IIC or applicable in presence of combustible dust

2): Frame size

71	71 mm
80	80 mm
90	90 mm
100	100 mm
112	112 mm
132	132 mm
160	160 mm
180	180 mm
200	200 mm
225	225 mm

3): Identifier for Motor-variation

4): Quantity of poles

5): Identifier for temperature control

CONDITIONS OF CERTIFICATION: YES as shown below:

The lengths of the flameproof joints are in parts longer and the gaps of the flameproof joints are in parts smaller than the values of table 2 of IEC 60079-1:2007. For information of the dimensions of the flameproof joints contact the manufacturer.

Fasteners with a minimum yield stress of 640 N/mm² must be used for the closing of the flameproof enclosure.

Motors which have to be equipped with a direct temperature control must be monitored by a separate certified trigger unit.

If the electrical machine will be cooled by forced ventilation, it has to be assured that the electrical machine can only run if the ventilation is running.



IECEX Certificate of Conformity

Certificate No.: IECEx BVS 14.0075X

Date of Issue: 2014-08-14

Issue No.: 0

Page 4 of 5

EQUIPMENT(continued):

Description

The enclosure of the flameproof electric motor is made of cast iron and has a mounting place for terminal boxes. The shaft will be fixed with ball bearings.

The shaft sealing of the flameproof electric motor is realised by non-metallic sealing rings made of viton for use in areas requiring EPL Db.

A terminal compartment in type of protection Flameproof enclosure "d", Increased safety "e" or Protection by enclosure "tb" or a direct cable entry is used for electrical connection of the motor. For electric power input into the motor compartment, separately certified cable glands or conductor bushings are used.

The cooling of the motor is realised by an external fan that is made of steel, aluminium or plastic. The fan can be driven by the electrical machine itself or by a separately certified forced ventilation motor.


Optionally a space heater can be mounted inside the stator housing.

For direct temperature monitoring the winding of the motor is equipped with temperature sensors (thermistors according DIN 44081 respectively DIN 44082). The sensors are connected in series.

Optionally the temperature at the bearings could be monitored separately certified resistance thermometers (Pt100).

The sensors respectively the thermometers will be connected to a trigger unit which is certified for this purpose.

The ambient temperature range is -30 °C to 85 °C. This temperature range may be limited as a result of the selected terminal boxes and components, or the electrical design.



IECEx Certificate of Conformity

Certificate No.: IECEx BVS 14.0075X

Date of Issue: 2014-08-14

Issue No.: 0

Page 5 of 5

Additional information:

Parameters

Electrical parameters

Circuits of the flameproof electric motors				
Rated voltage				
Frame size 71 - 225	up to	690	V AC	
Frame size 180 - 225	up to	1000	V AC	
Rated rotational speed	500	up to	3600	min ⁻¹
Rated rotational speed (with converter)	48	up to	6000	min ⁻¹
Frequency (mains)		50 / 60	Hz	
Frequency (converter)				
Frame size 71 - 160	5	up to	100	Hz
Frame size 180 - 225	5	up to	87	Hz
Duty type	S1	up to	S9	
Rated power				
Frame size		50 Hz	60 Hz	
71	up to	0.55 kW	0.66	kW
80	up to	1.1 kW	1.3	kW
90	up to	2.2 kW	2.6	kW
100	up to	3 kW	3.6	kW
112	up to	4 kW	4.8	kW
132	up to	7.5 kW	9	kW
160	up to	18.5 kW	21	kW
180	up to	22 kW	26	kW
200	up to	37 kW	42	kW
225	up to	45.5 kW	52	kW

Monitoring circuit

Temperature sensors
(ptc thermistors)

According to the specifications given in the certificate of
the trigger unit and the electrical design.

Circuits of the resistance thermometer (Pt100) According to the specifications given in the certificate of
the trigger unit and the electrical design.

Thermal ratings

Type of protection	Explosion-group	Lower limit	Upper limit
Ex d and Ex de	IIB / IIC	-20 °C	60 °C
Ex tb	IIIC	-30 °C	85 °C

Ambient temperature range, temperature class and surface temperature

The electrical data, the temperature class, the surface temperature and the ambient temperature range of the respective version is determined by a routine test carried out by the manufacturer.